



CLEAR VIEW PLUS 70

A multi-layered construction, this innovative film offers the highest performance possible from a clear, non-shiny film. It provides maximum infrared heat rejection and does not increase the shine of existing glass surfaces.

BENEFITS

Provides high infrared reflection instead of high infrared absorption.

Maintains a clear view inside and outside.

Preserves the non-reflective look of existing glass surfaces.

Virtually undetectable..



CLEAR VIEW PLUS 70

PERFORMANCE DATA

	SINGLE PANE	DUAL PANE
VISIBLE LIGHT:		
Visible Light Transmitted	72%	64%
Reflected Exterior	8%	15%
Reflected Interior	8%	12%

	SINGLE PANE	DUAL PANE
SOLAR ENERGY:		
Energy Transmitted	40%	38%
Energy Reflected	31%	29%
Energy Absorbed	29%	33%
UV Rejection	99%	99%
Total Solar Energy Rejected (TSER)	55%	51%
Infrared Heat Rejected	94%	94%
Shading Coefficient	0.52	0.56
Solar Heat Gain Coefficient	0.45	0.49
U Factor	0.90	0.47
Emissivity	0.77	0.77
Glare Reduction	20%	20%

The performance data above was tested according to ASTM & AIMCAL standards. All values represented are as applied on 1/8" (3mm) glass. Specific technical information can be found at WWW.XPEL.COM. For additional information contact SUPPORT@XPEL.COM.

WARRANTY INFORMATION

VISION Films are backed by a comprehensive warranty.



CLEAR VIEW PLUS 55

With a multi-layered construction, this innovative film offers the highest performance possible from a clear, non-shiny film. It provides maximum infrared heat rejection and does not increase the shine of your existing glass.

BENEFITS

Provides high infrared reflection instead of high infrared absorption.

Maintains a clear view inside and outside.

Preserves the non-reflective look of your current glass.

Can be virtually undetectable when installed on glass..



CLEAR VIEW PLUS 55

PERFORMANCE DATA

	SINGLE PANE	DUAL PANE
VISIBLE LIGHT:		
Visible Light Transmitted	58%	53%
Reflected Exterior	7%	14%
Reflected Interior	7%	11%

	SINGLE PANE	DUAL PANE
SOLAR ENERGY:		
Energy Transmitted	34%	30%
Energy Reflected	29%	27%
Energy Absorbed	37%	44%
UV Rejection	99%	99%
Total Solar Energy Rejected (TSER)	57%	51%
Infrared Heat Rejected	94%	94%
Shading Coefficient	0.50	0.57
Solar Heat Gain Coefficient	0.43	0.49
U Factor	0.90	0.47
Emissivity	0.78	0.78
Glare Reduction	34%	34%

The performance data above was tested according to ASTM & AIMCAL standards. All values represented are as applied on 1/8" (3mm) glass. Specific technical information can be found at WWW.XPEL.COM. For additional information contact SUPPORT@XPEL.COM.

WARRANTY INFORMATION

VISION Films are backed by a comprehensive warranty.



CLEAR VIEW PLUS 40

With a multi-layered construction, this innovative film offers the highest performance possible from non-shiny film. It provides maximum infrared heat rejection and does not increase the shine of your existing glass.

BENEFITS

Provides high infrared reflection instead of high infrared absorption.

Maintains a neutral view inside and outside.

Preserves increased glare reduction and privacy.

Can be virtually undetectable when installed on glass..



CLEAR VIEW PLUS 40

PERFORMANCE DATA

VISIBLE LIGHT:	SINGLE PANE	DUAL PANE
Visible Light Transmitted	40%	38%
Reflected Exterior	6%	13%
Reflected Interior	7%	8%

SOLAR ENERGY:	SINGLE PANE	DUAL PANE
Energy Transmitted	26%	24%
Energy Reflected	25%	27%
Energy Absorbed	49%	55%
UV Rejection	99%	99%
Total Solar Energy Rejected (TSER)	62%	52%
Infrared Heat Rejected	94%	94%
Shading Coefficient	0.44	0.55
Solar Heat Gain Coefficient	0.38	0.48
U Factor	0.89	0.47
Emissivity	0.75	0.77
Glare Reduction	53%	53%

The performance data above was tested according to ASTM & AIMCAL standards. All values represented are as applied on 1/8" (3mm) glass. Specific technical information can be found at WWW.XPEL.COM. For additional information contact SUPPORT@XPEL.COM.

WARRANTY INFORMATION

VISION Films are backed by a comprehensive warranty.



CLEAR VIEW PLUS 20

With a multi-layered construction, this innovative film offers the highest performance possible from non-shiny film. It provides maximum infrared heat rejection and does not increase the shine of your existing glass.

BENEFITS

- Provides high infrared reflection instead of high infrared absorption.
- Maintains a neutral view inside and outside.
- Preserves increased glare reduction and privacy.
- Can be virtually undetectable when installed on glass..



CLEAR VIEW PLUS 20

PERFORMANCE DATA

	SINGLE PANE	DUAL PANE
VISIBLE LIGHT:		
Visible Light Transmitted	21%	19%
Reflected Exterior	5%	13%
Reflected Interior	5%	6%

	SINGLE PANE	DUAL PANE
SOLAR ENERGY:		
Energy Transmitted	18%	15%
Energy Reflected	25%	24%
Energy Absorbed	57%	61%
UV Rejection	99%	99%
Total Solar Energy Rejected (TSER)	67%	53%
Infrared Heat Rejected	90%	90%
Shading Coefficient	0.38	0.54
Solar Heat Gain Coefficient	0.33	0.47
U Factor	0.94	0.45
Emissivity	0.66	0.66
Glare Reduction	77%	77%

The performance data above was tested according to ASTM & AIMCAL standards. All values represented are as applied on 1/8" (3mm) glass. Specific technical information can be found at WWW.XPEL.COM. For additional information contact SUPPORT@XPEL.COM.

WARRANTY INFORMATION

VISION Films are backed by a comprehensive warranty.