



DARK NEUTRAL 25

Designed to provide optimum heat and glare reduction, this neutral film provides privacy without the reflective silver look of conventional metal films.

BENEFITS

- Reduces glare by up to 89%.
- Provides extreme privacy and comfort.
- Very low interior reflection allows for better views, day and night.



DARK NEUTRAL 25

PERFORMANCE DATA

VISIBLE LIGHT:	SINGLE PANE	DUAL PANE
Visible Light Transmitted	27%	26%
Reflected Exterior	20%	25%
Reflected Interior	12%	13%

SOLAR ENERGY:	SINGLE PANE	DUAL PANE
Energy Transmitted	29%	26%
Energy Reflected	22%	20%
Energy Absorbed	49%	54%
UV Rejection	99%	99%
Total Solar Energy Rejected (TSER)	57%	47%
Infrared Heat Rejected	58%	58%
Shading Coefficient	0.50	0.61
Solar Heat Gain Coefficient	0.43	0.53
U Factor	0.96	0.47
Emissivity	0.75	0.76
Glare Reduction	70%	71%

The performance data above was tested according to ASTM & AIMCAL standards. All values represented are as applied on 1/8" (3mm) glass. Specific technical information can be found at WWW.XPEL.COM. For additional information contact SUPPORT@XPEL.COM.

WARRANTY INFORMATION

VISION Films are backed by a comprehensive warranty.



DARK NEUTRAL 15

Designed to provide optimum heat and glare reduction, this neutral film provides privacy without the reflective silver look of conventional metal films.

BENEFITS

- Reduces glare by up to 89%.
- Provides extreme privacy and comfort.
- Very low interior reflection allows for better views, day and night.



DARK NEUTRAL 15

PERFORMANCE DATA

	SINGLE PANE	DUAL PANE
VISIBLE LIGHT:		
Visible Light Transmitted	12%	10%
Reflected Exterior	20%	24%
Reflected Interior	13%	14%
SOLAR ENERGY:		
Energy Transmitted	18%	15%
Energy Reflected	30%	28%
Energy Absorbed	52%	57%
UV Rejection	99%	99%
Total Solar Energy Rejected (TSER)	70%	57%
Infrared Heat Rejected	75%	75%
Shading Coefficient	0.35	0.49
Solar Heat Gain Coefficient	0.30	0.43
U Factor	0.95	0.46
Emissivity	0.70	0.71
Glare Reduction	86%	90%

The performance data above was tested according to ASTM & AIMCAL standards. All values represented are as applied on 1/8" (3mm) glass. Specific technical information can be found at WWW.XPEL.COM. For additional information contact SUPPORT@XPEL.COM.

WARRANTY INFORMATION

VISION Films are backed by a comprehensive warranty.