



SECURITY CLEAR 4 MIL

Specifically designed to hold glass together in case of breakage, this film is constructed to handle direct force.

BENEFITS

Virtually clear glass protection.

Helps hold glass together in case of breakage.

Makes glass more difficult to penetrate.

Creates a safer area for work or play.



SAFETY CLEAR 4 MIL

PERFORMANCE DATA

VISIBLE LIGHT:		SINGLE PANE
Visible Light Transmitted		89%
Reflected Exterior		9%
Reflected Interior		9%

SOLAR ENERGY:		SINGLE PANE
Energy Transmitted		80%
Energy Reflected		8%
Energy Absorbed		12%
UV Rejection		99%
Total Solar Energy Rejected (TSER)		17%
Infrared Heat Rejected		N/A
Shading Coefficient		0.95
Solar Heat Gain Coefficient		0.83
U Factor		1.04
Emissivity		0.92
Glare Reduction		0%

SAFETY SPECS

30,000 (lb/in ²)	Tensile Strength
>2,500 (g/in)	Peel Strength
120 (lb/in)	Break Strength
70 (lbs)	Puncture Strength

The performance data above was tested according to ASTM & AIMCAL standards. All values represented are as applied on 1/8" (3mm) glass. Specific technical information can be found at WWW.XPEL.COM. For additional information contact SUPPORT@XPEL.COM.

WARRANTY INFORMATION

VISION Films are backed by a comprehensive warranty.